

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19



Supersedes N/A

Version 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Name: Kinepak Liquid

Intended Use of the Product

Detonating agent. For professional use only.

Name, Address, and Telephone of the Responsible Party

USA:

Dimension Supply, Inc.
1034 Oak Grove Rd
Morrisdale, PA 16858
1-814-343-4700

Emergency Telephone Numbers

Emergency number USA: 1-800-633-8253 (PERS) Customer #10351

IN THE US. FOR CHEMICAL EMERGENCIES (24 HOUR) INVOLVING TRANSPORTATION, SPILL, LEAK, RELEASE, FIRE OR ACCIDENTS. CALL: PERS 1-800-633-8253. Customer #10351

IN THE U.S. FOR LOST, STOLEN, OR MISPLACED EXPLOSIVES CALL: BATF 1-800-800-3855.

FORM ATF F 5400.5 MUST BE COMPLETED AND LOCAL AUTHORITIES (STATE/MUNICIPAL POLICE, ETC.) MUST BE ADVISED.

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 3	H226
Acute Tox. 4 (Oral)	H302
Acute Tox. 3 (Inhalation:gas)	H331
Carc. 1B	H350

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US):



GHS02



GHS06



GHS07



GHS08

Signal Word (GHS-US):

Danger

Hazard Statements (GHS-US):

H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H331 - Toxic if inhaled
H350 - May cause cancer

Precautionary Statements (GHS-US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist, spray, vapors, gas.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective clothing, protective gloves.
P301+P312 - If swallowed, call a doctor if you feel unwell.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P311 - Call a POISON CENTER or doctor.
P321 - Specific treatment (see Section 4).
P330 - If swallowed, rinse mouth.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) for extinction.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards Ingestion may cause methemoglobinemia. Initial manifestation of methemoglobinemia is cyanosis, characterized by navy lips, tongue and mucous membranes, with skin color being slate grey. Further manifestation is characterized by headache, weakness, dyspnea, dizziness, stupor, respiratory distress and death due to anoxia. If ingested, nitrates may be reduced to nitrites by bacteria in the digestive tract. Signs and symptoms of nitrite poisoning include methemoglobinemia, nausea, dizziness, increased heart rate, hypotension, fainting and, possibly shock.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Nitromethane	(CAS No) 75-52-5	98 - 100	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Carc. 1B, H350

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head positioned to avoid breathing in of vomit, rinse mouth and have victim drink plenty of water. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects Both Acute and Delayed

General: Harmful if swallowed. Toxic if inhaled.

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

Inhalation: Toxic if inhaled.

Skin Contact: May be harmful in contact with skin.

Eye Contact: May cause eye irritation.

Ingestion: Harmful if swallowed.

Chronic Symptoms: May cause cancer.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. Causes methemoglobinemia – emergency response should treat appropriately, such as by intravenous administration of methylene blue.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Normal fire: Dry chemical, alcohol foam, polymer foam, carbon dioxide, water spray, fog. When fire involves explosives: DO NOT ATTEMPT TO FIGHT FIRE.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Forms explosive mixtures in air. May darken on storage. May explode by detonation, heat or shock.

Advice for Firefighters

Precautionary Measures Fire: When mixed with incompatibles, this product can be an explosive with mass detonation hazard. DO NOT FIGHT FIRES INVOLVING EXPLOSIVE MATERIALS.

Firefighting Instructions: Normal fire: use water spray or fog for cooling exposed containers. When fire involves explosives: DO NOT ATTEMPT TO FIGHT FIRE. Immediately evacuate all personnel from the area to a safe distance. Guard against re-entry. Thermal decomposition can lead to release of irritating gases and vapors.

Protection During Firefighting: When controlling fire before involvement of explosives, fire-fighters should wear positive pressure self-containing breathing apparatus (SCBA) and full turnout gear.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides.

Other information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe dust or fumes. Keep away from heat, sparks, open flames, hot surfaces – No smoking. Eliminate every possible source of ignition. Evacuate danger area.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate danger area

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Hazardous waste due to potential risk of explosion.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Use only non-sparking tools. Be careful to avoid shock, friction, and contact with grit. Collect product for recovery or disposal. For release to land, contain discharge by constructing dykes or applying inert absorbent; for release to water, utilize damming and/or water diversion to minimize the spread of contamination. Collect contaminated soil and water, and absorbent for proper disposal. Notify applicable government authority if release is reportable or could adversely affect the environment.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: This product is a detonating agent and should only be used under the supervision of trained and licensed personnel. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities Not available

Technical Measures: Store as defined in the Explosives Act of Canada and the provisions of the Bureau of Alcohol, Tobacco and Firearms regulations contained in 27 CFR Part 555.

Storage Conditions: Store under moderate temperatures recommended by a technical services representative. Store under dry conditions in a well ventilated magazine that has been approved for either detonator storage or explosive storage. Keep away from heat, spark and flames. Keep containers closed. This product should be kept well away from initiating explosives; protected from physical damage; separated from incompatibles.

Special Rules on Packaging: Keep only in the original container.

Specific End Use(s)

Detonating agent. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Nitromethane (75-52-5)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	250 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA IDLH	US IDLH (ppm)	750 ppm
Alberta	OEL TWA (mg/m ³)	50 mg/m ³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m ³)	50 mg/m ³
New Brunswick	OEL TWA (ppm)	20 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m ³)	375 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m ³)	250 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	375 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m ³)	250 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m ³)	250 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Yukon	OEL STEL (mg/m ³)	375 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	250 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Proper grounding procedures to avoid static electricity should be followed. Product to be handled in a closed system and under strictly controlled conditions. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Dust/aerosol mask. Safety glasses.



Materials for Protective Clothing: Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing. Wear long sleeves.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, oily liquid
Odor	: Disagreeable and choking
Odor Threshold	: Not available
pH	: 6 - 8
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: -29°C/ -20.2°F (Nitromethane)
Freezing Point	: Not available
Boiling Point	: 100.8°C/ 213.4°F (Nitromethane)
Flash Point	: 35°C/ 95°F
Auto-ignition Temperature	: 77°C/ 170.6°F (Nitroethane)
Decomposition Temperature	: 210 °C (410 °F)
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: 63°C/ 145.4 °F (Nitroethane)
Vapor Pressure	: 3.7 kPa @ 20°C (Nitromethane)
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 1.14 (water = 1)
Specific Gravity	: 1.14
Solubility	: Partially soluble in methanol, diethyl ether. Slightly soluble in water.
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

SECTION 10: STABILITY AND REACTIVITY

Reactivity: May detonate if sensitized by amines, alkalies, strong acids, high temperatures or adiabatic compression.

Chemical Stability: Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials: May detonate if sensitized by amines, alkalies, strong acids, high temperatures or adiabatic compression. The dry alkali or amine salts are shock sensitive and sodium salt ignites on contact with water. Incompatible with amines, strong acids, strong bases, strong oxidizing agents, strong reducing agents, copper, copper alloys, lead, lead alloys. Flammable.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂), hydrocarbons, nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Harmful if swallowed. Toxic if inhaled.

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Toxic if inhaled.

Symptoms/Injuries After Skin Contact: May be harmful in contact with skin.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Harmful if swallowed.

Chronic Symptoms: May cause cancer. _

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Nitromethane (75-52-5)	
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (mg/l)	> 12.75 mg/l (Exposure time: 1 h)
Nitromethane (75-52-5)	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of carcinogenicity. Reasonably anticipated to be a human carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Nitromethane (75-52-5)	
LC50 Fish 1	460 mg/l (Exposure time: 48 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	450 mg/l (Exposure time: 24 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	36 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	< 278 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and Degradability Not available

Bioaccumulative Potential

Nitromethane (75-52-5)	
BCF fish 1	1.4
Log Pow	-0.34 - 0.17

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Destroy and dispose of in accordance with applicable local, state, provincial, territorial, federal and international regulations. Comply with regulations as defined in the Explosives Act of Canada and the provisions of the Bureau of Alcohol, Tobacco and Firearms regulations contained in 27 CFR part 555.

Ecology – Waste Materials: Hazardous waste due to toxicity.

EPA Hazardous Waste Number: D001, D003

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number

UN-No.(DOT): 1261

UN Proper Shipping Name

DOT Proper Shipping Name : Nitromethane

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard Labels (DOT) : 3 - Flammable liquids



Packing Group (DOT) : II - Medium Danger

Additional Information

Emergency Response Guide (ERG) Number : 129

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Kinepak Liquid	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Reactive hazard
Nitromethane (75-52-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	0.1 %

US State Regulations

Nitromethane (75-52-5)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Nitromethane (75-52-5)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Illinois - Toxic Air Contaminant Carcinogens U.S. - Illinois - Toxic Air Contaminants	

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

U.S. - Maine - Chemicals of High Concern
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
 U.S. - Massachusetts - Right To Know List
 U.S. - Michigan - Occupational Exposure Limits - TWAs
 U.S. - Michigan - Process Safety Management Highly Hazardous Chemicals
 U.S. - Minnesota - Chemicals of High Concern
 U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins
 U.S. - Minnesota - Hazardous Substance List
 U.S. - Minnesota - Permissible Exposure Limits - TWAs
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 U.S. - New Jersey - Environmental Hazardous Substances List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New Jersey - Special Health Hazards Substances List
 U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - New York - Priority Chemical Avoidance List
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
 U.S. - Wyoming - Process Safety Management - Highly Hazardous Chemicals

Canadian Regulations

Kinepak Liquid

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--



Nitromethane (75-52-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

Kinepak Liquid

Safety Data Sheet

according to HCS 29 CFR 1910.1200 Appendix D
Revision Date 09/18/19

Supersedes N/A

Version 1.0

SECTION 16: OTHER INFORMATION

Indication of Changes : 09/17/2013

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1B	Carcinogenicity Category 1B
Flam. Liq. 3	Flammable liquids Category 3
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H331	Toxic if inhaled
H350	May cause cancer

Party Responsible for the Preparation of This Document

Dimension Supply, Inc.
Morrisdale, PA. 16858

The information contained herein is provided only as a guide for the handling of this specific material and has been prepared in good faith by technically knowledgeable personnel. This Material Safety Data Sheet is not all-inclusive. The circumstances of use and handling may involve additional considerations that have not been addressed by this Data Sheet. No warranty of any kind is provided or implied by this Data Sheet. Dimension Supply, Inc. will not be liable for any damages, losses, injuries or indirect damages that may result from the use of, or reliance on, any information contained herein.